

SINOMACH

Equip the world and create value



Asphalt Paver GYA4500

MAIN FEATURES

- With hydraulic transmission system, which keeps the running more steady, guarantee paving quality;
- Auger helical distributor, full hydraulic control and adjustable height could be suitable for any working conditions;
- Independent hydraulic drive on both sides of track to make the paving on curved road and side slope more smoothly;
- It also can achieve spin turn and be convenient to turn around;
- The seat could be adjusted and move the machine, driver can observe the paving condition at any time.

GYA4500 Asphalt Paver

Main technical parameter

No	Item	GYA4500
1	Paving width	20.-4.5m step less adjustable
2	paving thickness	0-200mm
3	paving speed	0-20m/min
4	Running speed	0-4.5km/h
5	Max.productivity	150t/h
6	Engine power	93kW/2200rpm
7	Gross weight	10.5t
8	Hopper capacity	8t
9	Tamping frequency	25Hz

Engine

Dong Feng Cunnins model 4BTA3.9-C125,reasonable matching,suitable in any kind working site;
Powerful flywheel output,with big power reserve coefficient;
Low oil consumption,low noise,low pollution,strong overload capacity.

Operation control system

Favorable exchange interface between machines and driver;
Humanized design operation table can be moved to right-left,the seat could be adjusted and moved beyond the machine,so driver canobserve the paving condition at anytime.

Conveyor and auger

Two independent hydraulic systems drive right-left helical material distributor, full hydraulic helical material distributor; its height is adjustable and suitable for any working condition.
Two independent hydraulic systems drive right and left scraper, material feeding is convenient and prompt.

Traveling system

Imported pump,motor and speed reducer guarantee the reliability of transmission system;
Travelling system adopts double pumps,double motors,double speed reducers ;
Imported hydraulic plunger pump,italian imported planetary speed reducer;
Exchangeable rubber track plate.

Traveling system

Equipped with full hydraulic telescopic heavy duty mangle, paving width 2-4.5m,step less adjustable;
Gas heating achieves a quick temperature rise up;
The strong tamper can improve degree of compaction of paving materials;
Equip with ultrasonic leveling adjuster to reach optimum paving leveling.

SINOMACH-HI INTERNATIONAL EQUIPMENT COMPANY LIMITED

Add:No.898,Huanghe Road(West),Changzhou City,
Jiangsu Province,China.

P.C:213136

Tel:86-519-86781288 86752400

Fax:86-519-86781387

Http://www.sinomach-hi.com

E-mail:sales@changlin.com.cn service@changlin.com.cn

